


## PFR5102J630J11L16.5TR18

Aliases (F411JH102J630L)

PFR/F411, Film, Film/Foil Polypropylene, General Purpose, 1000 pF, 5%, 630 VDC, 85°C, Lead Spacing = 5mm



General Information		
Series	PFR/F411	
Dielectric	Film/Foil Polypropylene	
Style	Radial	
Features	Pulse	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	
Component Weight	0.382 g	
Miscellaneous	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult KEMET For Details.	

Click here for the 3D model.

Dimensions	
L	7.2mm -0.5mm
Н	6mm -0.5mm
Т	4.5mm -0.5mm
S	5mm +0.6/-0.1mm
НО	18.5mm +/-0.5mm
F	0.5mm +/-0.05mm
G	0.5mm NOM

Specifications	
Capacitance	1000 pF
Capacitance Tolerance	5%
Voltage AC	250 VAC
Voltage DC	630 VDC
Temperature Range	-55/+100°C
Rated Temperature	85°C
Dissipation Factor	0.04% 1kHz, 0.04% 10kHz, 0.05% 100kHz
Insulation Resistance	100 GOhms
Max dV/dt	1000 V/us
Inductance	6 nH

Packaging Specifications	
Packaging	T&R
Packaging Quantity	1500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)