

KEMET Part Number: PHE840EB5560KB04R17
(F840BD563K300A)

KEMET

a YAGEO company

PHE840E/F840, Film, Metallized Polypropylene, Safety, 0.056 uF, 10%, 300 VAC (X2), 760 VDC, 105°C, Lead Spacing = 15mm



Dimensions

| | |
|----|---------------|
| L | 18mm MAX |
| H | 10.5mm MAX |
| T | 5.5mm MAX |
| S | 15mm +/-0.4mm |
| LL | 17mm NOM |
| F | 0.8mm NOM |

Packaging Specifications

| | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 800 |

General Information

| | |
|-------------------------|--|
| Series: | PHE840E/F840 |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Safety Class: | X2 |
| Qualifications: | ENEC, UL, cUL |
| AEC-Q200: | No |
| THB Performance: | No |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

Specifications

| | |
|-------------------------------|------------------------------------|
| Capacitance: | 0.056 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 300 VAC (X2) |
| Voltage DC: | 760 VDC |
| Temperature Range: | -55/+105°C |
| Rated Temperature: | 105°C |
| Dissipation Factor: | 0.1% 1kHz, 0.2% 10kHz, 0.6% 100kHz |
| Insulation Resistance: | 30 GOhms |
| Max dV/dt: | 100 V/us |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET

a YAGEO company

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)