



Click [here](#) for the 3D model.

### Dimensions

|    |                    |
|----|--------------------|
| L  | 26.5mm +0.3/-0.5mm |
| H  | 17mm +0.1/-0.5mm   |
| T  | 8.5mm +0.2/-0.5mm  |
| S  | 22.5mm +/-0.4mm    |
| LL | 3.2mm +0.3/-0.2mm  |
| F  | 0.8mm +/-0.05mm    |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 468       |

### General Information

|                  |                                 |
|------------------|---------------------------------|
| Series           | R76                             |
| Dielectric       | Double Metallized Polypropylene |
| Style            | Radial                          |
| Features         | Automotive Grade, Pulse         |
| RoHS             | Yes                             |
| Lead             | Cut                             |
| Qualifications   | AEC-Q200                        |
| AEC-Q200         | Yes                             |
| Component Weight | 4.7 g                           |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 0.18 uF                                |
| Capacitance Tolerance | 5%                                     |
| Voltage AC            | 400 VAC                                |
| Voltage DC            | 630 VDC                                |
| Temperature Range     | -55/+110°C                             |
| Rated Temperature     | 85°C                                   |
| Dissipation Factor    | 0.03% 1kHz, 0.06% 10kHz                |
| Insulation Resistance | 100 GOhms                              |
| Max dV/dt             | 1500 V/us                              |
| Resistance            | 13.26 mOhms (100kHz)                   |
| Ripple Current        | 6.3 Amps (100kHz 85C), 270 Amps (Peak) |
| Inductance            | 16 nH                                  |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)