



Click [here](#) for the 3D model.

### Dimensions

L	57.5mm +/-1.2mm
H	50mm +/-1.2mm
T	35mm +/-1.2mm
S	52.5mm +/-0.4mm
S1	20.3mm +/-0.4mm
LL	6mm -2mm
F	1.2mm +/-0.05mm

### Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	23

### General Information

Series	C4AU
Dielectric	Metallized Polypropylene
Style	Radial
Features	DC Filtering
RoHS	Yes
Lead	4 Wire Leads
Qualifications	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200	Yes
Component Weight	136.5 g
Miscellaneous	Rth = 10 C/W.

### Specifications

Capacitance	55 uF
Capacitance Tolerance	5%
Voltage DC	800 VDC
Temperature Range	-55/+105°C
Insulation Resistance	550 MOhms
Max dV/dt	15 V/us
Resistance	3.6 mOhms (10kHz 70C)
Ripple Current	26.4 Amps Irms (10kHz 95C), 825 Amps Ipk
Inductance	15 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)