

No Drawing Available.  
Click [here](#) for the 3D model.

#### Dimensions

L	10.8mm +/-0.3mm
W	10mm +/-0.2mm
T	4mm MAX
LL	2mm NOM
G	4.7mm +/-0.3mm

#### Packaging Specifications

Packaging	T&R, 330mm
Packaging Quantity	500

#### General Information

Series	MPEV
Style	SMD
Chip Size	4340
Description	Surface Mount Inductor
Features	Power Inductors
Qualifications	AEC-Q200
AEC-Q200	Yes
Core	Composite
Miscellaneous	40 (K) Temperature Rise Max.

#### Specifications

Inductance	0.68 uH
Inductance Tolerance	20%
Temperature Range	-55/+180°C
Shielded	Yes
Current	23.1 A (Irms, 40C Rise By Self Heating), 23 A (Isat, 20% Drop In Inductance), 34.5 A (Isat, 30% Drop In Inductance)
DC Resistance	3.2 mOhms
Self-Resonant Frequency	47 MHz

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)