


FG1(25)-240X240T2900

Aliases (UFSFG12R5AT290)

KEMET, FG1, Flex Suppressors, Noise Suppression



Click here for the 3D model.

Dimensions	
Sheet Size	240x240mm
L	240mm NOM
W	240mm NOM
Т	0.025mm NOM

Packaging Specifications	
Tape Description	Without PET Tape (Txx00)
Tape Thickness	0.01mm
Component Weight	10.69 g

General Information		
Series	FG1	
Style	Sheet	
Description	Flex Suppressor GHz Band High Performance Type	
Features	GHz Band High Performance Type, Wi-Fi, GPS, LTE-A	
RoHS	Yes	
Qualifications	UL94 HB, UL File No. E176124	
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free	

Specifications	
Temperature Range	-40/+105°C
Permeability	25 u At 3MHz
Effective Frequency	1 GHz to 10 GHz
Specific Gravity	3.1 TYP
Surface Resistivity	1 MOhm/sq. TYP

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)