

PHE426HR8200JR04L2

Aliases (F426RP206J250CL40J)

PHE426/F426, Film, Metallized Polypropylene, General Purpose, 20 uF, 5%, 250 VDC, 85°C, Lead Spacing = 37.5mm



Click here for the 3D model.

Dimensions	
L	41mm MAX
н	38mm MAX
т	21mm MAX
S	37.5mm +/-0.5mm
LL	4mm NOM
F	1mm NOM

Packaging Specifications	
Packaging	Tray
Packaging Quantity	84

General Information		
Series	PHE426/F426	
Dielectric	Metallized Polypropylene	
Style	Radial	
Features	Pulse	
RoHS	Yes	
Lead	Wire Leads	
AEC-Q200	No	
Component Weight	34.4 g	
Notes Not For New Design, Please Check Possible Alternative Parts (AltPart).		

Specifications			
Capacitance	20 uF		
Capacitance Tolerance	5%		
Voltage AC	160 VAC		
Voltage DC	250 VDC, 185 VDC (105C)		
Temperature Range	-55/+105°C		
Rated Temperature	85°C		
Dissipation Factor	0.1% 1kHz		
Insulation Resistance	1.5 GOhms		
Max dV/dt	30 V/us		
Inductance	6 nH		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)