


## FMOV473ZF-L1

FM, Supercapacitors, Radial Molded, 0.047 F, -20/+80%, 3.5 VDC, Bent, Lead Spacing = 5mm



Click here for the 3D model.

Dimensions	
W	10.5mm +/-0.5mm
Н	11.5mm +/-0.5mm
Т	5mm +/-0.5mm
S	5mm +/-0.5mm
G	0.4mm +/-0.1mm
LT1	0.5mm +/-0.1mm
LT2	0.4mm +/-0.1mm

Packaging Specifications	
Lead	Bent
Packaging	Bulk, Box
Packaging Quantity	1000

General Information		
Series	FM	
Description	Radial Molded Double Layer Capacitor	
RoHS	Yes	
AEC-Q200	No	
Component Weight	1.3 g	
Miscellaneous	DischargeValue = 0.06 F.	

Specifications	
Capacitance	0.047 F
Capacitance Tolerance	-20/+80%
Voltage DC	3.5 VDC
Temperature Range	-25/+70°C
Rated Temperature	70°C
Resistance	200000 mOhms (1kHz)
Discharge Current	0.042 mAmps (30 Minutes After Charging)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)