

**KEMET Part Number: C0805X472K5RACTU**  
(C0805X472K5RAC7800)

SMD Comm X7R Flex, Ceramic, 4700 pF, 10%, 50 VDC, X7R, SMD, MLCC, FT-CAP, Temperature Stable, 0805



**Dimensions**

| Dimensions |                  |
|------------|------------------|
| Chip Size  | 0805             |
| L          | 2mm +/-0.3mm     |
| W          | 1.25mm +/-0.3mm  |
| T          | 0.78mm +/-0.20mm |
| S          | 0.75mm MIN       |
| B          | 0.5mm +/-0.25mm  |

**Packaging Specifications**

|                     |                          |
|---------------------|--------------------------|
| Packaging:          | T&R, 180mm, Plastic Tape |
| Packaging Quantity: | 4000                     |

**General Information**

|                   |                                       |
|-------------------|---------------------------------------|
| Series:           | SMD Comm X7R Flex                     |
| Style:            | SMD Chip                              |
| Description:      | SMD, MLCC, FT-CAP, Temperature Stable |
| Features:         | FT-CAP, Temperature Stable            |
| RoHS:             | Yes                                   |
| Termination:      | Flexible Termination                  |
| Marking:          | No                                    |
| AEC-Q200:         | No                                    |
| Component Weight: | 13 mg                                 |
| Shelf Life:       | 78 Weeks                              |
| MSL:              | 1                                     |

**Specifications**

|   |   |
|---|---|
| Capacitance:  | 4700 pF   |
| Measurement Condition:  | 1 kHz 1.0Vrms                                   |
| Capacitance Tolerance:  | 10%   |
| Voltage DC:   | 50 VDC  |
| Dielectric Withstanding Voltage:                                    | 125 VDC   |
| Temperature Range:  | -55/+125°C                                      |
| Temperature Coefficient:  | X7R   |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 15%, 1kHz 1.0Vrms                               |
| Dissipation Factor:   | 2.5% 1 kHz 1.0Vrms                              |
| Aging Rate:   | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance:  | 100 GOhms                                       |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)