

**KEMET Part Number: R71QW4820AA10K**  
(71QW4820AA10K)

R71, Film, Metallized Polypropylene, General Purpose, 8.2 uF, 10%, 1000 VDC, 105°C, Lead Spacing = 37.5mm



#### Dimensions

L	41.5mm +0.3/-0.7mm
H	44mm +0.1/-0.7mm
T	24mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

#### Packaging Specifications

Packaging:	Tray
Packaging Quantity:	108

#### General Information

Series:	R71
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	PFC and Pulse
RoHS:	Yes
Lead:	Cut
AEC-Q200:	No
Miscellaneous:	Above 105C DC And AC Voltage Derating Is 4%/C.

#### Specifications

Capacitance:	8.2 uF
Capacitance Tolerance:	10%
Voltage AC:	275 VAC
Voltage DC:	1000 VDC
Temperature Range:	-40/+110°C
Rated Temperature:	105°C
Dissipation Factor:	0.1% 25C
Insulation Resistance:	3.6585 GOhms
Max dV/dt:	80 V/us
Resistance:	52.4 mOhms (100kHz)
Ripple Current:	3.01 Amps (100kHz 85C), 656 Amps (Peak)
Inductance:	20 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)