
KEMET Part Number: PEH200OL4150MB2



PEH200, Aluminum Electrolytic, 1,500 uF, 20%, 420 VDC, -40/+85°C



Dimensions	
D	76.6mm +/-1mm
L	77mm +/-1mm
Т	3.8mm NOM
S	32mm +/-0.5mm
DT	15mm NOM
LT	84mm +/-1mm
Z	13mm NOM

Packaging Specifications		
Sleeving:	Yes	
Packaging:	Bulk, Bag	
Packaging Quantity:	9	

General Information		
Series:	PEH200	
Dielectric:	Aluminum Electrolytic	
Description:	Screw Terminal, Aluminum Electrolytic	
RoHS:	Yes	
Mounting:	Stud	
AEC-Q200:	No	
Halogen Free:	Yes	
Component Weight:	430 g	
Notes:	Dimensions D And L Include Sleeving. MS = M12x16.	
Shelf Life:	156 Weeks	

Specifications		
Capacitance:	1,500 uF	
Capacitance Tolerance:	20%	
Voltage DC:	420 VDC	
Temperature Range:	-40/+85°C	
Rated Temperature:	85°C	
Life:	19000 Hrs (Rated Voltage And	
	Ripple Current At 85C)	
Resistance:	47 mOhms (100Hz 20C), 23	
Resistance	mOhms (100kHz 20C)	
	9.1 Amps (100Hz 85C), 42.3	
Ripple Current:	Amps (10kHz 50C), 28.5 Amps	
	(10kHz 40C)	
Leakage Current:	5890 uA (5min 20°C)	
Inductance:	17 nH (ESL)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

- >>KEMET(基美)
- 〉〉点击查看相关商品