

PHE840MT7330MF18R04L2

Aliases (F840FT335M275CL40J)

PHE840M/F840, Film, Metallized Polypropylene, Safety, 3.3 uF, 20%, 275 VAC (X2), 760 VDC, 105°C, Lead Spacing = 27.5mm



Click here for the 3D model.

Dimensions	
L	31.5mm MAX
Н	19mm MAX
Т	31mm MAX
S	27.5mm +/-0.4mm
LL	4mm NOM
F	0.8mm NOM

Packaging Specifications	
Packaging	Tray
Packaging Quantity	72

General Information	
Series	PHE840M/F840
Dielectric	Metallized Polypropylene
Style	Radial
Features	EMI Safety
RoHS	Yes
Lead	Wire Leads
Safety Class	X2
Qualifications	ENEC, UL, cUL
AEC-Q200	No
THB Performance	No
Component Weight	20.23 g
Notes	Not For New Design, Please Check Possible Alternative Parts (AltPart).

Specifications			
Capacitance	3.3 uF		
Capacitance Tolerance	20%		
Voltage AC	275 VAC (X2)		
Voltage DC	760 VDC		
Temperature Range	-55/+105°C		
Rated Temperature	105°C		
Dissipation Factor	0.1% 1kHz, 0.8% 10kHz		
Insulation Resistance	3.0303 GOhms		
Max dV/dt	100 V/us		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)