



Click [here](#) for the 3D model.

Dimensions

| | |
|-------------|---------------|
| D | 10mm +/-0.5mm |
| L | 12.5mm +1.5mm |
| S | 5mm +/-0.5mm |
| LL Negative | 15mm MIN |
| LL Positive | 20mm MIN |
| F | 0.6mm NOM |

Packaging Specifications

| | |
|--------------------|------|
| Packaging | T&R |
| Packaging Quantity | 1200 |

General Information

| | |
|-------------|------------------------------------|
| Series | ESK |
| Dielectric | Aluminum Electrolytic |
| Description | Single Ended Aluminum Electrolytic |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |

Specifications

| | |
|-------------------------|--------------------------|
| Capacitance | 3.3 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 450 VDC, 500 VDC (Surge) |
| Temperature Range | -25/+85°C |
| Rated Temperature | 85°C |
| Life | 2000 Hrs |
| Dissipation Factor | 24% 120Hz 20C |
| Ripple Current | 40 mAmps (120Hz 85C) |
| Leakage Current | 54.55 uA (2min 20°C) |
| Impedance Ratio at -25C | 15 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)