



Click [here](#) for the 3D model.

### Dimensions

|    |                         |
|----|-------------------------|
| L  | 7.37mm +/-0.25mm        |
| H  | 7.37mm +/-0.25mm        |
| T  | 2.29mm +/-0.25mm        |
| S  | 5.08mm +/-0.38mm        |
| LL | 31.75mm MIN             |
| F  | 0.635mm +0.102/-0.051mm |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 100       |

### General Information

|                |  |
|----------------|--|
| Series         | LDD Comm COG   |
| Style          | Radial   |
| Features       | Commercial   |
| RoHS           | No   |
| Prop 65        | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> |
| SCIP Number    | 8c864fd1-202b-4ce7-85fd-56c9e19121ad   |
| Termination    | Lead (SnPb)  |
| Qualifications | EIA, UL  |
| AEC-Q200       | No   |

### Specifications

|                                 |               |
|---------------------------------|---------------|
| Capacitance                     | 3900 pF       |
| Capacitance Tolerance           | 10%           |
| Voltage DC                      | 100 VDC       |
| Dielectric Withstanding Voltage | 250 VDC       |
| Temperature Range               | -55/+125°C    |
| Temperature Coefficient         | COG           |
| Dissipation Factor              | 0.1% 1kHz 25C |
| Insulation Resistance           | 256 MOhms     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)