


FX5(50)-240X240T2900 Aliases (UFSFX5005AT290)

KEMET, FX5, Flex Suppressors, Noise Suppression



General Information		
Series	FX5	
Style	Sheet	
Description	Flex Suppressor High Permeability Type	
Features	High Permeability Type	
RoHS	Yes	
Qualifications	UL94 HB, UL File No. E176124	
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free	

Specifications	
Temperature Range	-40/+105°C
Permeability	150 u At 3MHz
Effective Frequency	1 MHz to 3GHz
Specific Gravity	3.3 TYP
Surface Resistivity	1MOhm/sq. TYP

Click here for the 3D model.

x240mm
mm NOM
mm NOM
imm NOM

Packaging Specifications		
Tape Description	Without PET Tape (Txx00)	
Tape Thickness	0.01mm	
Component Weight	15.73 g	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)