



Dimensions

| | |
|----|------------------|
| L | 18mm +0.3/-0.5mm |
| H | 12mm +0.1/-0.5mm |
| T | 6mm +0.2/-0.5mm |
| S | 15mm +/-0.4mm |
| LL | 25mm +2/-1mm |
| F | 0.6mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 900 |

General Information

| | |
|-----------------|--------------------------|
| Series | R46 310 VAC 125C |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | EMI Safety |
| RoHS | Yes |
| Lead | Wire Leads |
| Safety Class | X2 |
| Qualifications | ENEC, UL, cUL, CQC |
| AEC-Q200 | No |
| THB Performance | No |

Specifications

| | |
|-----------------------|--------------|
| Capacitance | 0.15 μ F |
| Capacitance Tolerance | 10% |
| Voltage AC | 310 VAC (X2) |
| Voltage DC | 630 VDC |
| Temperature Range | -40/+125°C |
| Rated Temperature | 125°C |
| Dissipation Factor | 0.2% 1KHz |
| Insulation Resistance | 10 GOhms |
| Max dV/dt | 400 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)