



Click [here](#) for the 3D model.

### Dimensions

|    |               |
|----|---------------|
| L  | 18mm MAX      |
| H  | 12mm MAX      |
| T  | 6mm MAX       |
| S  | 15mm +/-0.4mm |
| LL | 30mm NOM      |
| F  | 0.8mm NOM     |

### Packaging Specifications

Packaging Bulk, Bag

### General Information

|            |  |
|------------|--|
| Series     | PHE426/F426  |
| Dielectric | Metallized Polypropylene   |
| Style      | Radial   |
| Features   | Pulse  |
| RoHS       | Yes  |
| Lead       | Wire Leads   |
| AEC-Q200   | No   |
| Notes      | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

### Specifications

|                       |                          |
|-----------------------|--------------------------|
| Capacitance           | 0.33 uF                  |
| Capacitance Tolerance | 5%                       |
| Voltage AC            | 160 VAC                  |
| Voltage DC            | 250 VDC, 185 VDC (105C)  |
| Temperature Range     | -55/+105°C               |
| Rated Temperature     | 85°C                     |
| Dissipation Factor    | 0.05% 1kHz, 0.25% 100kHz |
| Insulation Resistance | 100 GOhms                |
| Max dV/dt             | 450 V/us                 |
| Inductance            | 6 nH                     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)