



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 32mm +0.3/-0.7mm |
| H  | 28mm +0.1/-0.7mm |
| T  | 14mm +0.2/-0.7mm |
| S  | 27.5mm +/-0.4mm  |
| LL | 4mm +2mm         |
| F  | 0.8mm +/-0.05mm  |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 352  |

### General Information

|                  |                              |
|------------------|------------------------------|
| Series           | R52 310 VAC MINI             |
| Dielectric       | Metallized Polypropylene     |
| Style            | Radial                       |
| Features         | EMI Safety                   |
| RoHS             | Yes                          |
| Lead             | Wire Leads                   |
| Safety Class     | X2                           |
| Qualifications   | ENEC, UL, cUL, CQC, AEC-Q200 |
| AEC-Q200         | Yes                          |
| THB Performance  | Yes                          |
| Component Weight | 17.28 g                      |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 4.7 uF       |
| Capacitance Tolerance | 20%          |
| Voltage AC            | 310 VAC (X2) |
| Voltage DC            | 630 VDC      |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.2% 1KHz    |
| Insulation Resistance | 141 GOhms    |
| Max dV/dt             | 150 V/us     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)