



Click [here](#) for the 3D model.

General Information

Series	SMD Mil PRF55681
Style	SMD Chip
RoHS	No
Prop 65	⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov .
Termination	Lead (SnPb)
Failure Rate	P (0.1%/1000 Hrs)
Testing and Reliability	MIL-PRF-55681
Qualifications	MIL-PRF-55681
AEC-Q200	No
Miscellaneous	Termination Description: SolderPlate 70-30.
Shelf Life	78 Weeks
MSL	1

Specifications

Capacitance	0.12 uF
Capacitance Tolerance	10%
Voltage DC	100 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	BX

Dimensions

Chip Size	1825
L	4.57mm +0.38/-0.51mm (0.18 in +0.015/-0.02 in)
W	6.35mm +0.38/-0.51mm (0.25 in +0.015/-0.02 in)
T	1.27mm +/-0.76mm (0.05 in +/-0.03 in)
B	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

Packaging Specifications

Packaging	T&R, 178mm, Plastic Tape
Packaging Quantity	1100

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)