


F5AJC4100AAI6K

Aliases (5AJC4100AAI6K)

rol Information

F5A, Film, Metallized Polyester, Varistor/Capacitor, 1 uF, 10%, 30 VDC, 100°C, Lead Spacing = 5mm



General mormation		
Series	F5A	
Dielectric	Metallized Polyester	
Style	Radial	
Features	EMI-RFI suppressors for DC motors	
RoHS	Yes	
Lead	Wire Leads	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Miscellaneous	The Rated Voltage Decreases 2%/C Between +100C And +125C. Varistor= 47 VDC.	

Specifications	,
Capacitance	1uF
Capacitance Tolerance	10%
Voltage DC	30 VDC, 15 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	100°C
Dissipation Factor	1% 1kHz

Click here for the 3D model.

Dimensions	
L	7.5mm MAX
Н	10.1mm MAX
Т	5.1mm MAX
S	5mm +/-0.4mm
LL	4mm +2mm
F	0.6mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)