
KEMET Part Number: R73TW3150JB00J

(73TW3150JB00J)



R73, Film, Film/Foil Polypropylene, General Purpose, 0.15 uF, 5%, 1600 VDC, 85°C, Lead Spacing = 37.5mm



Dimensions		
L	41.5mm +0.3/-0.7mm	
Н	28.5mm +0.1/-0.7mm	
Т	16mm +0.3/-0.7mm	
S	37.5mm +/-0.4mm	
LL	3.5mm +0.5mm	
F	1mm +/-0.05mm	

Packaging Specifications	
Packaging:	Tray
Packaging Quantity:	216

General Information		
Series:	R73	
Dielectric:	Film/Foil Polypropylene	
Style:	Radial	
Features:	Pulse	
RoHS:	Yes	
Lead:	Cut	
AEC-Q200:	No	
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.	

Specifications		
Capacitance:	0.15 uF	
Capacitance Tolerance:	5%	
Voltage AC:	450 VAC	
Voltage DC:	1600 VDC	
Temperature Range:	-55/+105°C	
Rated Temperature:	85°C	
Dissipation Factor:	0.03% 1kHz, 0.06% 10kHz	
Insulation Resistance:	100 GOhms	
Max dV/dt:	6500 V/us	
Inductance:	20 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)