KEMET Part Number: R463F2470DQH1K

(463F2470DQH1K)



R46 310 VAC 125C, Film, Metallized Polypropylene, Safety, 0.047 uF, 10%, 310 VAC (X2), 630 VDC, 125°C, Lead Spacing = 10mm



General Information	
Series:	R46 310 VAC 125C
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Safety Class:	X2
Qualifications:	ENEC, UL, cUL, CQC
AEC-Q200:	No
THB Performance:	No

Dimensions		
L	13mm +0.2/-0.5mm	
Н	12mm +0.1/-0.5mm	
Т	6mm +0.2/-0.5mm	
S	10mm +/-0.4mm	
Н0	18.5mm +/-0.5mm	
F	0.6mm +/-0.05mm	

Specifications	
Capacitance:	0.047 uF
Capacitance Tolerance:	10%
Voltage AC:	310 VAC (X2)
Voltage DC:	630 VDC
Temperature Range:	-40/+125°C
Rated Temperature:	125°C
Dissipation Factor:	0.3% 1kHz
Insulation Resistance:	100 GOhms
Max dV/dt:	500 V/us

Packaging Specifications		
Packaging:	Ammo, 360x340x59mm, Box	
Packaging Quantity:	680	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



5cb58

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)