


PEH169, Aluminum Electrolytic, 330 uF, -10/+30%, 400 VDC, -40/+85°C



General Information	
Series:	PEH169
Dielectric:	Aluminum Electrolytic
Description:	Screw Terminal, Aluminum Electrolytic
RoHS:	Yes
Mounting:	Stud
AEC-Q200:	No
Halogen Free:	Yes
Component Weight:	180 g
Notes:	Dimensions D And L Include Sleeving. M5. MS = M12x16.
Shelf Life:	156 Weeks

Dimensions	
D	51.6mm +/-1mm
L	74.5mm +/-1mm
T	4.9mm NOM
S	22mm +/-0.5mm
F	15mm +/-0.5mm
DT	15mm NOM
G	13mm NOM
LT	82.4mm +/-1mm
Z	13mm NOM

Specifications	
Capacitance:	330 uF
Capacitance Tolerance:	-10/+30%
Voltage DC:	400 VDC
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	17000 Hrs (Rated Voltage And Ripple Current At 85C)
Resistance:	230 mOhms (100Hz 20C), 110 mOhms (100kHz 20C)
Ripple Current:	3.3 Amps (100Hz 85C), 15.1 Amps (10kHz 50C), 11.3 Amps (10kHz 40C)
Leakage Current:	4396 uA (5min 20°C)
Inductance:	16 nH (ESL)

Packaging Specifications	
Sleeving:	Yes
Packaging:	Bulk, Bag
Packaging Quantity:	20

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)