



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 11mm +/-0.2mm    |
| L2 | 2.96mm MAX       |
| W  | 12.2mm +/-0.2mm  |
| H  | 6.05mm +/-0.2mm  |
| H1 | 9.25mm +1mm      |
| S  | 10mm +/-0.2mm    |
| S1 | 2.54mm +/-0.2mm  |
| S2 | 5.08mm +/-0.2mm  |
| LL | 3.2mm +1mm       |
| F  | 0.5mm +/-0.05mm  |
| E  | 0.2mm MAX        |
| G  | 0.3mm MAX        |
| X  | 0.35mm +/-0.05mm |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tube |
| Packaging Quantity | 43   |

### General Information

|            |                      |
|------------|----------------------|
| Series     | MDK/F68              |
| Dielectric | Metallized Polyester |
| Style      | Dual-In-Line         |
| RoHS       | Yes                  |
| Lead       | Wire Leads           |
| AEC-Q200   | No                   |

### Specifications

|                       |                                  |
|-----------------------|----------------------------------|
| Capacitance           | 1.2 uF                           |
| Capacitance Tolerance | 10%                              |
| Voltage AC            | 63 VAC                           |
| Voltage DC            | 100 VDC                          |
| Temperature Range     | -55/+125°C                       |
| Rated Temperature     | 85°C                             |
| Dissipation Factor    | 0.8% 1kHz, 1.5% 10kHz, 5% 100kHz |
| Insulation Resistance | 4.1667 GOhms                     |
| Inductance            | 4 nH                             |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)