


ALC40, Aluminum Electrolytic, 820 uF, 20%, 350 VDC, -40/+105°C



**Dimensions**

<b>D</b>	35mm +1mm
<b>L</b>	80mm +/-2mm
<b>S</b>	10mm +/-0.1mm
<b>LL</b>	4mm +/-1mm
<b>F</b>	2mm +/-0.1mm

**Packaging Specifications**

<b>Packaging:</b>	Bulk, Bag
-------------------	-----------

**General Information**

<b>Series:</b>	ALC40
<b>Dielectric:</b>	Aluminum Electrolytic
<b>Description:</b>	Snap-In, Aluminum Electrolytic
<b>RoHS:</b>	Yes
<b>Lead:</b>	2 Pin Short
<b>AEC-Q200:</b>	No
<b>Component Weight:</b>	105 g
<b>Shelf Life:</b>	156 Weeks

**Specifications**

<b>Capacitance:</b>	820 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	350 VDC, 385 VDC (Surge)
<b>Temperature Range:</b>	-40/+105°C
<b>Rated Temperature:</b>	105°C
<b>Life:</b>	8000 Hrs (Rated Voltage And Ripple Current At 105C), 13000 Hrs (Rated Voltage At 105C)
<b>Resistance:</b>	150 mOhms (100Hz 20C), 102 mOhms (10kHz 20C)
<b>Ripple Current:</b>	3.82 Amps (100Hz 105C), 6.72 Amps (10kHz 105C)
<b>Leakage Current:</b>	861 uA (5min 20°C)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)