

### FRONT VIEW



### SIDE VIEW



Click [here](#) for the 3D model.

#### Dimensions

|    |             |
|----|-------------|
| D  | 21mm MAX    |
| L  | 44mm MAX    |
| LL | 40mm +/-5mm |
| F  | 1mm NOM     |

#### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 100       |

#### General Information

|                  |                                    |
|------------------|------------------------------------|
| Series           | C4G                                |
| Dielectric       | Metallized Polypropylene           |
| Style            | Axial                              |
| Features         | Switching                          |
| RoHS             | Yes                                |
| Lead             | Wire Leads                         |
| AEC-Q200         | No                                 |
| Component Weight | 14 g                               |
| Miscellaneous    | Polyester Tape & Resin Protection. |

#### Specifications

|                       |                                      |
|-----------------------|--------------------------------------|
| Capacitance           | 4.7 uF                               |
| Capacitance Tolerance | 10%                                  |
| Voltage AC            | 250 VAC                              |
| Voltage DC            | 400 VDC                              |
| Temperature Range     | -40/+85°C                            |
| Rated Temperature     | 70°C                                 |
| Dissipation Factor    | 0.05%                                |
| Max dV/dt             | 30 V/us                              |
| Resistance            | 4.1 mOhms (100kHz)                   |
| Ripple Current        | 9 Amps (100kHz 70C), 141 Amps (Peak) |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)