


## CKC18C943KCGLC7210

KONNEKT KC-Link, Ceramic, 0.094 uF, 10%, 500 VDC, COG, 2-Chip Standard Orientation.



Click here for the 3D model.

Dimensions	
L	4.5mm +/-0.3mm
W	3.2mm +/-0.3mm
Т	5.1mm +/-0.4mm
В	0.6mm +/-0.35mm

Packaging Specifications			
Packaging	T&R, 330mm		
Packaging Quantity	900		

General Information		
Series	KONNEKT KC-Link	
Style	KONNEKT	
Description	SMD, MLCC, Ultra-Stable, Low Loss, Class I	
Features	Ultra-Stable, Low Loss	
RoHS	Yes	
Termination	Tin	
AEC-Q200	No	
Component Weight	300 mg	
Notes	2-Chip Standard Orientation.	
Chip Size	1812	
MSL	1	

Specifications			
Capacitance	0.094 uF		
Measurement Condition	1 kHz 1.0Vrms		
Capacitance Tolerance	10%		
Voltage DC	500 VDC		
Dielectric Withstanding Voltage	750 VDC		
Temperature Range	-55/+150°C		
Temperature Coefficient	COG		
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30 ppm/C, 1kHz 1.0Vrms		
Dissipation Factor	0.1% 1 kHz 1.0Vrms		
Aging Rate	0% Loss/Decade Hour		
Insulation Resistance	11 MOhms		


Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



CKC18C943KCGLC7210 KONNEKT KC-Link, Ceramic, 0.094 uF, 10%, 500 VDC, C0G, 2-Chip Standard Orientation.


## Simulations

For the complete simulation environment please visit K-SIM.





**CKC18C943KCGLC7210** KONNEKT KC-Link, Ceramic, 0.094 uF, 10%, 500 VDC, COG, 2-Chip Standard Orientation.





KONNEKT KC-Link, Ceramic, 0.094 uF, 10%, 500 VDC, COG, 2-Chip Standard Orientation.

## These are simulations.

This is not a specification!

The responses shown represent the typical response for each part type. Specific responses may vary, depending on manufacturing variation affects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.

The responses shown do not represent a specified or implied maximum capability of the device for all applications.

- The ESR used for ripple "Ripple Current/Voltage vs. Frequency" plots is the ESR at ambient temperature.
- The ESR in the "Temperature Rise vs. Ripple Current" plots is adjusted to each incremental temperature rise before the power and ripple current is calculated.
- The effects shown herein are based on measured data from a multiple part sample of the parts in question.
- Ripple capability of this device will be factored by thermal resistance (Rth) created by circuit traces (addi affects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance. The peak voltages generated in the "Temperature Rise vs. Combined Ripple Currents" plot are calculated for each frequency and are not combined with voltages generated at any other
- harmonics.
- Please consult with the catalog or field applications engineer for maximum capability of the device in specific applications.

All product information and data (collectively, the "Information") are subject to change without notice.

KEMET K-SIM is designed to simulate behavior of components with respect to frequency, ambient temperature, and DC bias levels. The responses shown represent the typical response for each part type. Specific responses may vary, depending on manufacturing variation effects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.

All Information given herein is believed to be accurate and reliable, but is presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

If you have any questions please contact K-SIM.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)