



Click [here](#) for the 3D model.

### Dimensions

L	12.2mm +/-0.2mm
L2	2.29mm MAX
W	16.5mm +/-0.2mm
H	6.05mm +/-0.2mm
H1	9.25mm +1mm
S	15mm +/-0.2mm
S1	2.54mm +/-0.2mm
S2	7.62mm +/-0.2mm
LL	3.2mm +1mm
F	0.5mm +/-0.05mm
E	0.2mm MAX
G	0.3mm MAX
X	0.35mm +/-0.05mm

### Packaging Specifications

Packaging	Tube
Packaging Quantity	39

### General Information

Series	MDK/F68
Dielectric	Metallized Polyester
Style	Dual-In-Line
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No

### Specifications

Capacitance	0.33 uF
Capacitance Tolerance	10%
Voltage AC	200 VAC
Voltage DC	400 VDC
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.5% 10kHz, 5% 100kHz
Insulation Resistance	30 GOhms
Inductance	4 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)