



Click [here](#) for the 3D model.

Dimensions

L	11mm +/-0.2mm
L2	2.96mm +/-0.2mm
W	12.2mm +/-0.2mm
H	6.05mm +/-0.2mm
H1	6.6mm +/-0.4mm
S	10mm +/-0.2mm
S1	2.54mm +/-0.2mm
S2	5.08mm +/-0.2mm
LL	0.55mm +/-0.2mm
F	0.5mm +/-0.05mm
E	0.2mm MAX
G	0.3mm MAX
X	0.35mm +/-0.05mm
Y	2.6mm +/-0.2mm
Z	1.5mm +/-0.2mm

Packaging Specifications

Packaging	Tube
Packaging Quantity	43

General Information

Series	MDS
Dielectric	Metallized Polyester
Style	Dual-In-Line
RoHS	Yes
Lead	L Leads
AEC-Q200	No

Specifications

Capacitance	0.18 uF
Capacitance Tolerance	10%
Voltage AC	160 VAC
Voltage DC	250 VDC
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.5% 10kHz, 5% 100kHz
Insulation Resistance	30 GOhms
Inductance	4 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)