



Click [here](#) for the 3D model.

### Dimensions

L	14.2mm MAX
W	9.2mm MAX
H	5.4mm MAX
LL	2.8mm +/-0.1mm
S	7.62mm +/-0.2mm
S1	2.54mm +/-0.2mm
F	0.5mm +/-0.1mm
F1	0.25mm +/-0.1mm

### Packaging Specifications

Packaging	Bulk
-----------	------

### General Information

Series	EA2
Style	Through-Hole
Description	Miniature Signal Relay, Non-latch
Features	Compact Size, Flat-Package. FCC (1500 V) surge capacity. UL recognized and CSA certified. Low power consumption (100-200 mW)
RoHS	Yes
Coil Type	Single Coil (Non-Latching)

### Specifications

Temperature Range	-40/+85°C
Coil Voltage	3 V
Coil Resistance	64.3 Ohms +/-10%
Contact Form	2 Form C (DPDT)
Contact Material	Silver Alloy With Gold Alloy Overlay
Voltage Characteristics	2.25 (Operate) / 0.3 (Release)
Switching Power	30 W, 62.5 VA
Switching Voltage DC	220 V
Switching Voltage AC	250 VAC
Switching Current	1 A
Contact Current Class	>10A
Carrying Current	2 Amps
Contact Resistance	75 mOhms
Operation Time	Approximately 2ms
Release Time	Approximately 1ms
Insulation Resistance	1 GOhms
Withstanding Voltage	1000 VAC (1min) 1500 V Surge
Miscellaneous	Not Available, Please Contact MFG for other options

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)