


A759, Polymer Aluminum, 12 uF, 20%, 63 VDC, -55/+125°C, Lead Spacing = 2.5mm



Dimensions	
D	6.3mm +/-0.5mm
L	5mm +/-1mm
S	2.5mm +/-0.5mm
LL Negative	15mm MIN
LL Positive	19mm MIN
F	0.45mm +/-0.05mm

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1000

General Information	
Series:	A759
Dielectric:	Polymer Aluminum
Description:	Single Ended, Polymer Aluminum
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Halogen Free:	Yes

Specifications	
Capacitance:	12 uF
Capacitance Tolerance:	20%
Voltage DC:	63 VDC, 72.4 VDC (Surge)
Temperature Range:	-55/+125°C
Rated Temperature:	125°C
Life:	2000 Hrs (+/-20% Initial Capacitance, 1.5x DF MAX, Leakage Within Limit)
Dissipation Factor:	12% 120Hz 20C
Resistance:	60 mOhms (100kHz 20C)
Ripple Current:	1658 mAmps (100kHz 105C), 975 mAmps (100kHz 125C)
Leakage Current:	151 uA (2min 20°C)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)