
KEMET Part Number: PEG124PA147CQL1



PEG124, Aluminum Electrolytic, 4.7 uF, -10/+30%, 100 VDC, -40/+105°C





Dimensions		
D	10mm +/-0.5mm	
L	20mm +/-1mm	
L1	26mm MIN	
LL	31mm +3/-2mm	
F	0.8mm +/-0.03mm	

Packaging Specifications		
Sleeving:	Yes	
Packaging:	Bulk, Bag	

General Information		
Series:	PEG124	
Dielectric:	Aluminum Electrolytic	
Style:	Axial	
Description:	Long Life Axial Aluminum Electrolytic	
Features:	Long Life	
RoHS:	Yes	
Lead:	Wire Leads	
AEC-Q200:	No	
Halogen Free:	Yes	
Component Weight:	3 g	
Miscellaneous:	Life Calculation Based On Maximum Ripple Current, Please Contact KEMET For More Information.	
Notes:	L1 is KEMETs recommendation for minimum distance between symmetrical Lead bend. Available only for Customer specific part numbers. Lead bend dimensions must be specified and confirmed per article. Dimensions D And L Include Sleeving.	
Shelf Life:	156 Weeks	

Specifications		
Capacitance:	4.7 uF	
Capacitance Tolerance:	-10/+30%	
Voltage DC:	100 VDC	
Temperature Range:	-40/+105°C	
Rated Temperature:	105°C	
Life:	8000 Hrs	
Resistance:	16000 mOhms (100Hz 20C), 2800 mOhms (100kHz 20C)	
Ripple Current:	0.05 Amps (100Hz 105C), 0.65 Amps (5kHz 60C), 0.2 Amps (5kHz 105C)	
Leakage Current:	5 uA (5min 20°C)	
Inductance:	5 nH (ESL)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)