


C340C394K1R5HA

GoldMax 300 Comm X7R, Ceramic, 0.39 uF, 10%, 100 VDC, X7R, GoldMax, Commercial Standard, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	7.36mm MAX
н	10.16mm MAX
т	4.07mm MAX
S	5.08mm +/-0.78mm
LL	7mm MIN
F	0.51mm +0.1/-0.025mm

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	100

General Information		
Series	GoldMax 300 Comm X7R	
Style	Radial	
Description	GoldMax, Commercial Standard	
RoHS	No	
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	d4c83dcf-0af3-4f6a-8c42-c840cabd6f5b	
Termination	Lead (SnPb)	
Failure Rate	N/A	
AEC-Q200	No	
Halogen Free	Yes	

Specifications			
Capacitance	0.39 uF		
Measurement Condition	1 kHz 1.0Vrms		
Capacitance Tolerance	10%		
Voltage DC	100 VDC		
Dielectric Withstanding Voltage	250 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	X7R		
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	0.15, 1kHz 1.0Vrms		
Dissipation Factor	2.5%1 kHz 1.0Vrms		
Aging Rate	3% Loss/Decade Hour		
Insulation Resistance	2.56 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)