
KEMET Part Number: ALS41G682NT350



ALS41, Aluminum Electrolytic, 6,800 uF, 20%, 350 VDC, -40/+105°C



Dimensions	
D	77mm +/-1mm
L	220mm +/-2mm
Т	6.4mm +/-0.5mm
S	31.8mm +/-0.5mm
DT	17mm +/-0.5mm
LT	Available On Request
TD	11.8mm MIN
V	19mm NOM

Packaging Specifications		
Sleeving:	Yes	
Packaging:	Bulk, Box	

General Information		
Series:	ALS41	
Dielectric:	Aluminum Electrolytic	
Description:	Screw Terminal, Aluminum Electrolytic	
RoHS:	Yes	
Mounting:	Stud	
AEC-Q200:	No	
Halogen Free:	Yes	
Component Weight:	1.45 kg	
Notes:	Dimensions D And L Include Sleeving. MS (MxH) = M12x16.	
Shelf Life:	156 Weeks	

Specifications		
Capacitance:	6,800 uF	
Capacitance Tolerance:	20%	
Voltage DC:	350 VDC, 385 VDC (Surge)	
Temperature Range:	-40/+105°C	
Rated Temperature:	105°C	
Life:	9000 Hrs (Rated Voltage And Ripple Current At 105C), 15000 Hrs (Rated Voltage At 105C)	
Resistance:	23 mOhms (100Hz 20C), 17 mOhms (10kHz 20C)	
Ripple Current:	25.4 Amps (100Hz 105C), 35.7 Amps (10kHz 105C)	
Leakage Current:	6000 uA (5min 20°C)	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)