



Click [here](#) for the 3D model.

### Dimensions

|    |                    |
|----|--------------------|
| L  | 26.5mm +0.3/-0.5mm |
| H  | 20mm +0.1/-0.5mm   |
| T  | 11mm +0.2/-0.5mm   |
| S  | 22.5mm +/-0.4mm    |
| LL | 25mm +2/-1mm       |
| F  | 0.8mm +/-0.05mm    |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 250       |

### General Information

|                 |                              |
|-----------------|------------------------------|
| Series          | R52 310 VAC MINI             |
| Dielectric      | Metallized Polypropylene     |
| Style           | Radial                       |
| Features        | EMI Safety                   |
| RoHS            | Yes                          |
| Lead            | Wire Leads                   |
| Safety Class    | X2                           |
| Qualifications  | ENEC, UL, cUL, CQC, AEC-Q200 |
| AEC-Q200        | Yes                          |
| THB Performance | Yes                          |

### Specifications

|                       |              |
|-----------------------|--------------|
| Capacitance           | 1.5 uF       |
| Capacitance Tolerance | 20%          |
| Voltage AC            | 310 VAC (X2) |
| Voltage DC            | 630 VDC      |
| Temperature Range     | -40/+110°C   |
| Rated Temperature     | 110°C        |
| Dissipation Factor    | 0.2% 1KHz    |
| Insulation Resistance | 45 GOhms     |
| Max dV/dt             | 200 V/us     |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)