
KEMET Part Number: 05HS33B155KC

(05HS33B155KC)



HS RAD-LDD Space X7R HV, Ceramic, 1.5 uF, 10%, 500 VDC, X7R, Lead Spacing = 17.78mm



Dimensions		
L	21.59mm MAX	
Н	10.16mm MAX	
Т	6.89mm MAX	
S	17.78mm +/-0.762mm	
LL	31.75mm MIN	
F	0.635mm NOM	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1	

General Information		
Series:	HS RAD-LDD Space X7R HV	
Style:	Radial	
RoHS:	No	
Prop 65:	warning: Cancer and reproductive harm - www.p65warnings.ca.gov.	
SCIP Number:	2340ecb8-2b2f-4a8e-990d- e9ce728f4668	
Termination:	Lead (SnPb)	
Failure Rate:	N/A	
Testing and Reliability:	CSAM	
AEC-Q200:	No	
Notes:	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.	

Specifications		
Capacitance:	1.5 uF	
Capacitance Tolerance:	10%	
Voltage DC:	500 VDC	
Dielectric Withstanding Voltage:	750 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	X7R	
Dissipation Factor:	2.5%	
Insulation Resistance:	666.667 MOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)