




VCR Indust COG HVHT200C, Ceramic, 150 pF, 10%, 3000 VDC, COG, Commercial, High Temperature, HighVoltage, Lead Spacing = 6.35mm



Click here for the 3D model.

Dimensions	
L	8.89mm MAX
W	10.16mm MAX
т	6.98mm MAX
S	6.35mm +/-0.76mm
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	1	

General Information	
Series	VCR Indust COG HVHT200C
Style	Radial
Description	Commercial, High Temperature, HighVoltage
Features	High Temperature, High Voltage, Commercial
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm – http://www.p65warnings.ca.gov.
SCIP Number	8b930311-e6ed-4436-9857-2b5f449be092
Termination	Lead (SnPb)
Failure Rate	N/A
Testing and Reliability	MIL-PRF-20 Group A
Qualifications	MIL-PRF-20 Group A
AEC-Q200	No

Specifications				
Capacitance	150 pF			
Capacitance Tolerance	10%			
Voltage DC	3000 VDC			
Dielectric Withstanding Voltage	4500 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	COG			
Dissipation Factor	0.15% 1 kHz 1.0Vrms			
Insulation Resistance	100 GOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)