
KEMET Part Number: R73PI21504000K

(73PI21504000K)



R73, Film, Film/Foil Polypropylene, Automotive Grade, 0.015 uF, 10%, 630 VDC, 85°C, Lead Spacing = 15mm



General Information			
Series:	R73		
Dielectric:	Film/Foil Polypropylene		
Style:	Radial		
Features:	Automotive Grade, Pulse		
RoHS:	Yes		
Lead:	Wire Leads		
Qualifications:	AEC-Q200		
AEC-Q200:	Yes		
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.		

11000 V/us

10 nH

Max dV/dt: Inductance:

Dimensions		
L	18mm +0.3/-0.5mm	
Н	12mm +0.1/-0.5mm	
Т	6mm +0.2/-0.5mm	
S	15mm +/-0.4mm	
LL	30mm +5mm	
F	0.8mm +/-0.05mm	

]	Specifications	
8mm +0.3/-0.5mm		Capacitance:	0.015 uF
mm +0.1/-0.5mm		Capacitance Tolerance:	10%
mm +0.2/-0.5mm		•	
L5mm +/-0.4mm		Voltage AC:	300 VAC
		Voltage DC:	630 VDC
30mm +5mm		Temperature Range:	-55/+105°C
.8mm +/-0.05mm		Rated Temperature:	85°C
		Dissipation Factor:	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz
cations		Insulation Resistance:	100 GOhms

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	900	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



7a18c

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)