


MPLCV0654L470

Aliases (UPIT0654L47000)

KEMET, MPLCV, Power, 47 uH, 20%, 0654(3126)



Click here for the 3D model.

Dimensions	
L	7.9mm MAX
W	6.7mm +/-0.4mm
Т	5.4mm MAX

Packaging Specifications		
Packaging	T&R, 380mm	
Packaging Quantity	1000	

General Information		
Series	MPLCV	
Style	SMD	
Chip Size	0654(3126)	
Description	Surface Mount Inductor	
Features	Power Inductors, Automotive	
RoHS	Yes	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Core	Composite	
Miscellaneous	40 (K) Temperature Rise Max.	

Specifications	
Inductance	47 uH
Inductance Tolerance	20%
Temperature Range	-55/+155°C
Shielded	Yes
Current	3 A (Isat, 30% Drop In Inductance), 2.1 A (Irms, 40C Rise By Self Heating)
DC Resistance	175 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)