



Click [here](#) for the 3D model.

### Dimensions

|    |              |
|----|--------------|
| L  | 7.2mm MAX    |
| H  | 8mm MAX      |
| T  | 3.5mm MAX    |
| S  | 5mm +/-0.4mm |
| LL | 5mm NOM      |
| F  | 0.5mm NOM    |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 2000      |

### General Information

|                  |  |
|------------------|--|
| Series           | MMK/F601   |
| Dielectric       | Metallized Polyester   |
| Style            | Radial   |
| Features         | DC Multipurpose Applications   |
| RoHS             | Yes  |
| Lead             | Wire Leads   |
| AEC-Q200         | No   |
| Component Weight | 0.354 g  |
| Notes            | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

### Specifications

|                       |                                    |
|-----------------------|------------------------------------|
| Capacitance           | 2200 pF                            |
| Capacitance Tolerance | 10%                                |
| Voltage AC            | 250 VAC                            |
| Voltage DC            | 1000 VDC, 775 VDC (100C)           |
| Temperature Range     | -55/+100°C                         |
| Rated Temperature     | 85°C                               |
| Dissipation Factor    | 0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz |
| Insulation Resistance | 30 GOhms                           |
| Max dV/dt             | 100 V/us                           |
| Inductance            | 6 nH                               |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)