



Click [here](#) for the 3D model.

### Dimensions

|    |                   |
|----|-------------------|
| D  | 8.92mm +/-0.25mm  |
| L  | 19.96mm +/-0.79mm |
| L2 | 23.42mm MAX       |
| LL | 38.1mm +/-6.35mm  |
| F  | 0.64mm +/-0.05mm  |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Tray |
| Packaging Quantity | 20   |

### General Information

|                |  |
|----------------|--|
| Series         | T256 CSS33   |
| Dielectric     | MnO2 Tantalum  |
| Style          | Axial Hermetic   |
| Description    | Axial, Solid Tantalum, Hermetically Sealed, Military, CSS33 Style  |
| Features       | Extended Capacitance, Low Leakage  |
| RoHS           | No   |
| Prop 65        | <b>⚠ WARNING:</b> Cancer and reproductive harm - <a href="http://www.p65warnings.ca.gov">http://www.p65warnings.ca.gov</a> . |
| SCIP Number    | bee1eed4-5fec-4214-9f43-620c5b22071f   |
| Termination    | Lead (SnPb)  |
| Lead           | Wire Leads   |
| Qualifications | CSS33  |
| AEC-Q200       | No   |
| Construction   | Hermetic   |
| Notes          | Dimensions Include Insulating Sleeve. Caution: Black Band Indicates Negative End Of Case.                                    |

### Specifications

|                       |                      |
|-----------------------|----------------------|
| Capacitance           | 470 uF               |
| Capacitance Tolerance | 10%                  |
| Voltage DC            | 10 VDC (85C)         |
| Temperature Range     | -55/+125°C           |
| Dissipation Factor    | 10%                  |
| Failure Rate          | B (0.1%/1000 Hrs)    |
| Resistance            | 0.065 Ohms (100kHz)  |
| Ripple Current        | 1664 mAmps (100 kHz) |
| Leakage Current       | 4 uA                 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)