




### BOTTOM VIEW



CATHODE (-) END VIEW



SIDE VIEW

Click [here](#) for the 3D model.

### Dimensions

L	24.5mm +/-0.5mm
W	8.5mm +/-0.5mm
H	9.1mm +/-0.5mm
S	3mm +/-0.3mm
F	4.2mm +/-0.5mm

### Packaging Specifications

Packaging	Bulk, Box
Packaging Quantity	100

### General Information

Series	T555
Dielectric	Polymer Tantalum
Style	SMD Chip
RoHS	No
SCIP Number	43449f08-bd3e-4b72-a04c-6ca7dd4144ff
Termination	Tin
AEC-Q200	No
Component Weight	5.54 g
Shelf Life	156 Weeks

### Specifications

Capacitance	330 uF
Capacitance Tolerance	10%
Voltage DC	35 VDC, 27.3 VDC (105°C), 40.25 VDC (85°C)
Temperature Range	-55/+105°C
Dissipation Factor	10% (120Hz 25C)
Failure Rate	N/A
Resistance	180 mOhm (100kHz 25C)
Ripple Current	1240 mAmps (40kHz 85C)
Leakage Current	86.6 uA (5min 25°C)
Testing and Reliability	25C +/-5C, 10 Cycles, After Constant Voltage Conditioning (KEMET Standard)

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)