

		Т
	W	
L		

General Information			
Series	M4		
Style	Sheet		
Description	Flex Suppressor Halogen Free Type		
Features	High Magnetic Permeability Type, Low Magnetic Loss Type		
RoHS	Yes		
Qualifications	UL94 HB, UL File No. E176124		
Environment	Halogen Free, PVC Free, Lead Free, Red Phosphorus Free		

Specifications	
Temperature Range	-40/+105°C
Permeability	40 u At 13.56MHz
Effective Frequency	13.56 MHz and below
Specific Gravity	3.1TYP
Surface Resistivity	10 MOhm/sq. TYP

Click here for the 3D model.

Dimensions	
Sheet Size	240mmx20M
L	20000mm NOM
W	240mm NOM
Т	0.3mm NOM

Packaging Specifications	
Tape Description	No Adhesive Tape
Component Weight	4.17583 kg

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)