



Click [here](#) for the 3D model.

| Dimensions |                    |
|------------|--------------------|
| L          | 26.5mm +0.3/-0.5mm |
| H          | 20mm +0.1/-0.5mm   |
| T          | 11mm +0.2/-0.5mm   |
| S          | 22.5mm +/-0.4mm    |
| LL         | 25mm +2/-1mm       |
| F          | 0.8mm +/-0.05mm    |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 250       |

| General Information |                                 |
|---------------------|---------------------------------|
| Series              | R76                             |
| Dielectric          | Double Metallized Polypropylene |
| Style               | Radial                          |
| Features            | Automotive Grade, Pulse         |
| RoHS                | Yes                             |
| Lead                | Wire Leads                      |
| Qualifications      | AEC-Q200                        |
| AEC-Q200            | Yes                             |

| Specifications        |  |
|-----------------------|--|
| Capacitance           | 0.1 uF                                 |
| Capacitance Tolerance | 5%                                     |
| Voltage AC            | 650 VAC                                |
| Voltage DC            | 1600 VDC                               |
| Temperature Range     | -55/+110°C                             |
| Rated Temperature     | 85°C                                   |
| Dissipation Factor    | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz   |
| Insulation Resistance | 100 GOhms                              |
| Max dV/dt             | 3000 V/us                              |
| Resistance            | 11.14 mOhms (100kHz)                   |
| Ripple Current        | 7.3 Amps (100kHz 85C), 300 Amps (Peak) |
| Inductance            | 16 nH                                  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)