



Click [here](#) for the 3D model.

Dimensions

L	41.5mm +0.3/-0.7mm
H	32mm +0.1/-0.7mm
T	19mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

Packaging Specifications

Packaging	Tray
Packaging Quantity	192

General Information

Series	R71
Dielectric	Metallized Polypropylene
Style	Radial
Features	PFC and Pulse
RoHS	Yes
Lead	Cut
AEC-Q200	No
Component Weight	30.28 g
Miscellaneous	Above 105C DC And AC Voltage Derating Is 4%/C.

Specifications

Capacitance	3.9 uF
Capacitance Tolerance	5%
Voltage AC	275 VAC
Voltage DC	1000 VDC
Temperature Range	-40/+110°C
Rated Temperature	105°C
Dissipation Factor	0.1% 25C
Insulation Resistance	7.6923 GOhms
Max dV/dt	120 V/us
Resistance	85.7 mOhms (100kHz)
Ripple Current	2.23 Amps (100kHz 85C), 468 Amps (Peak)
Inductance	20 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)