

C4AU, Film, Metallized Polypropylene, Automotive DC Link, 23 uF, 5%, 1100 VDC, Lead Spacing = 52.5mm



General Information	
Series:	C4AU
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	DC Filtering
RoHS:	Yes
Lead:	4 Wire Leads
Qualifications:	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200:	Yes
Miscellaneous:	Rth = 12 C/W.

Dimensions	
L	57.5mm +/-1.2mm
H	45mm +/-1.2mm
T	30mm +/-1.2mm
S	52.5mm +/-0.4mm
S1	20.3mm +/-0.4mm
LL	6mm -2mm
F	1.2mm +/-0.05mm

Specifications	
Capacitance:	23 uF
Capacitance Tolerance:	5%
Voltage DC:	1100 VDC
Temperature Range:	-55/+105°C
Insulation Resistance:	1.3 GOhms
Max dV/dt:	20 V/us
Resistance:	6.1 mOhms (10kHz 70C)
Ripple Current:	18.8 Amps Irms (10kHz 95C), 460 Amps Ipk
Inductance:	13 nH

Packaging Specifications	
Packaging:	Bulk, Box
Packaging Quantity:	27

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)