
## KEMET Part Number: C1206X153MCGACAUTO



SMD Auto C0G HV Flex, Ceramic, 0.015 uF, 20%, 500 VDC, C0G, SMD, MLCC, FT-CAP, Ultra-Stable, Automotive Grade, 1206



Dimensions	
Chip Size	1206
L	3.3mm +/-0.4mm
W	1.6mm +/-0.35mm
т	1.6mm +/-0.25mm
В	0.6mm +/-0.25mm

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	2000	

General Information		
Series:	SMD Auto COG HV Flex	
Style:	SMD Chip	
Description:	SMD, MLCC, FT-CAP, Ultra- Stable, Automotive Grade	
Features:	FT-CAP, Ultra-Stable, Automotive Grade	
RoHS:	Yes	
Termination:	Flexible Termination	
Marking:	No	
Qualifications:	AEC-Q200	
AEC-Q200:	Yes	
Shelf Life:	78 Weeks	
MSL:	1	

Specifications		
Capacitance:	0.015 uF	
Measurement Condition:	1 kHz 1.0Vrms	
Capacitance Tolerance:	20%	
Voltage DC:	500 VDC	
Dielectric Withstanding Voltage:	750 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	30 ppm/C, 1kHz 1.0Vrms	
Dissipation Factor:	0.1% 1kHz 1.0Vrms	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	66.667 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)