

KEMET Part Number: R75RW41804030M
(75RW41804030M)

R75, Film, Metallized Polypropylene, General Purpose, 1.8 uF, 20%, 1250 VDC, 85°C, Lead Spacing = 37.5mm



General Information	
Series:	R75
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	Pulse
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.

Dimensions	
L	41.5mm +0.3/-0.7mm
H	44mm +0.1/-0.7mm
T	24mm +0.3/-0.7mm
S	37.5mm +/-0.4mm
LL	30mm +5mm
F	1mm +/-0.05mm

Packaging Specifications	
Packaging:	Tray
Packaging Quantity:	72

Specifications	
Capacitance:	1.8 uF
Capacitance Tolerance:	20%
Voltage AC:	600 VAC
Voltage DC:	1250 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.06% 1kHz
Insulation Resistance:	16.6667 GOhms
Max dV/dt:	360 V/us
Resistance:	2.7 mOhms (100KHz)
Ripple Current:	20.92 Amps (100kHz 85C), 990 Amps (Peak)
Inductance:	20 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)