## **KEMET Part Number: C0805X822JAGACTU**

(C0805X822JAGAC7800)



SMD Comm C0G Flex, Ceramic, 8200 pF, 5%, 250 VDC, C0G, SMD, MLCC, FT-CAP, Ultra-Stable, 0805



| Dimensions |                  |  |
|------------|------------------|--|
| Chip Size  | 0805             |  |
| L          | 2mm +/-0.3mm     |  |
| W          | 1.25mm +/-0.3mm  |  |
| Т          | 1.25mm +/-0.15mm |  |
| S          | 0.75mm MIN       |  |
| В          | 0.5mm +/-0.25mm  |  |

| Packaging Specifications |                          |  |
|--------------------------|--------------------------|--|
| Packaging:               | T&R, 180mm, Plastic Tape |  |
| Packaging Quantity:      | 2500                     |  |

| General Information |                                     |  |
|---------------------|-------------------------------------|--|
| Series:             | SMD Comm C0G Flex                   |  |
| Style:              | SMD Chip                            |  |
| Description:        | SMD, MLCC, FT-CAP, Ultra-<br>Stable |  |
| Features:           | FT-CAP, Ultra-Stable                |  |
| RoHS:               | Yes                                 |  |
| Termination:        | Flexible Termination                |  |
| Marking:            | No                                  |  |
| AEC-Q200:           | No                                  |  |
| Component Weight:   | 14 mg                               |  |
| Shelf Life:         | 78 Weeks                            |  |
| MSL:                | 1                                   |  |

| Specifications  |                        |  |
|---|------------------------|--|
| Capacitance:  | 8200 pF                |  |
| Measurement Condition:  | 1 kHz 1.0Vrms          |  |
| Capacitance Tolerance:  | 5%                     |  |
| Voltage DC:   | 250 VDC                |  |
| Dielectric Withstanding<br>Voltage:                                 | 625 VDC                |  |
| Temperature Range:  | -55/+125°C             |  |
| Temperature Coefficient:  | COG                    |  |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 30 ppm/C, 1kHz 1.0Vrms |  |
| Dissipation Factor:   | 0.1% 1 kHz 1.0Vrms     |  |
| Aging Rate:   | 0% Loss/Decade Hour    |  |
| Insulation Resistance:  | 100 GOhms              |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



## 单击下面可查看定价,库存,交付和生命周期等信息

## >>KEMET(基美)