
KEMET Part Number: R73UR2120SE00J

(73UR2120SE00J)



R73, Film, Film/Foil Polypropylene, General Purpose, 0.012 uF, 5%, 2000 VDC, 85°C, Lead Spacing = 27.5mm



General Information	
Series:	R73
Dielectric:	Film/Foil Polypropylene
Style:	Radial
Features:	Pulse
RoHS:	Yes
Lead:	Cut
AEC-Q200:	No
Miscellaneous:	Above 85C DC And AC Voltage Derating Is 1.25%/C.

Dimensions		
L	32mm +0.3/-0.7mm	
Н	17mm +0.1/-0.7mm	
Т	9mm +0.2/-0.7mm	
S	27.5mm +/-0.4mm	
LL	4mm +2mm	
F	0.8mm +/-0.05mm	

Packaging Specifications	
Packaging:	Tray
Packaging Quantity:	816

Specifications	
Capacitance:	0.012 uF
Capacitance Tolerance:	5%
Voltage AC:	500 VAC
Voltage DC:	2000 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz
Insulation Resistance:	100 GOhms
Max dV/dt:	11000 V/us
Inductance:	18 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2022 KEMET

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)